



MAC-2D Soft Ride Diesel Transporter

Dimensions:	Height: 37 - 40 ½" Width: 4'-0" Length: 12'-6" Turning Radius: 12' I.S. Ground Clearance: 9" Standard	Drive:	Hydrostatic, using dual wheel drive units mounted on support tube with planetary gearing, integral spring-applied brake, Wheel unit capacity 6000 lbs
Weight:	2000#	Suspension:	Front – Rubber mounted A frame style axle with Soft Ride air suspension and heavy-duty gas shocks. Automotive Type tie rods. Rear – HD leaf springs with heavy duty gas shocks and rubber overload bumpers.
Payload:	2000#, 2 Men	Fire Suppression:	Standard - Ansul manual actuated with engine shutoff. Optional – Ansul automatic/manual actuated with engine shutoff "Check Fire System"
Performance:	Speed 15 mph. Maximum operating grade 18%	Fire Extinguisher:	#10 fire extinguisher, bracket and guard
Engine:	Deutz F2L2011, 2 cylinder, 30 HP at 2800 rpm, oil cooled, heavy duty industrial design, certified by MSHA for use in underground mining under Part 7, Title 30 CFR. Outby use only	Tires:	Front: 23x850x12 -6 Ply / 27x850x15 -8 Ply Rear: 26x1200x12 -8 Ply / 10-16.5 -8 Ply
Electrical:	12 Volt	Capacities:	Diesel fuel – 9.85 gallons. Hydraulic oil – 9.6 gallons
Headlights:	Two front, two rear, halogen, 12volt	Options:	Canopy, SCSR Storage, Winch, Seating, and Tires. Contact Mfg. For more...
Brakes:	Four-wheel wet disc brakes, spring applied, pressure release w/ automatic parking brake feature, Rear hydrostatic holdback.		